



INTRODUCING

SpeedCouple

PRE-INSTALLED SWIVEL COUPLING

DURAGUARD™ RIGID, IMC AND ELBOWS

Faster.

Same functionality as a three-piece coupling or split bolt

Features easy lead-in threads

Flexibility.

Great for tight spots, saddles, offsets, trenches and duct banks

Available on 10' and 20' DuraGuard rigid, IMC and elbows
Trade sizes 2-5 | Straight runs and elbows | Listed as concrete tight

Give it a turn!

Turn SpeedCouple, not the conduit or elbows.

Watch the video at wheatland.com/speedcouple and try SpeedCouple on your next project.

Material and labor savings can be up to

50%

when compared to three-piece couplings.



Wheatland Tube

JMC STEEL GROUP

Know better. Know Wheatland.



SpeedCouple: Pre-installed Swivel Coupling



Available on 10' and 20' DuraGuard™ rigid, IMC and elbows

Trade sizes for DuraGuard rigid and elbows: 2-5

Trade sizes for IMC: 2-4

Straight runs and elbows

Listed as concrete tight

The engineered steel factory-installed SpeedCouple swivel coupling connects in as little as half the time of conventional couplings. Just turn SpeedCouple, not the heavy conduit or elbows, and let the lead-in threads do most of the work. Eliminate purchasing inventory and installation of couplings. It's easier on your crew and your budget!

Watch the video at wheatland.com/speedcouple

WEIGHTS, DIMENSIONS AND PACKAGING FOR SPEEDCOUPLE ON GALVANIZED RIGID CONDUIT (GRC)

TRADE SIZE	OD*	ID*	lbs./ft.	MASTER BUNDLES — 10'			MASTER BUNDLES — 20'		
				ft.	pieces	lbs.	ft.	pieces	lbs.
2	2.375	2.083	3.32	450	45	1494	600	30	1992
2½	2.875	2.489	5.27	400	40	2108	360	18	1897
3	3.500	3.090	6.82	300	30	2046	300	15	2046
3½	4.000	3.570	8.31	250	25	2078	240	12	1994
4	4.500	4.050	9.72	200	20	1944	200	10	1944
5	5.563	5.073	13.14	150	15	1971	140	7	1840

*Note: SpeedCouple GRC shall be listed to safety standards UL-6 and UL-514B. Manufactured in accordance with ANSI C80.1.

WEIGHTS, DIMENSIONS AND PACKAGING FOR SPEEDCOUPLE ON INTERMEDIATE METAL CONDUIT (IMC)

TRADE SIZE	OD*	ID*	lbs./ft.	MASTER BUNDLES — 10'		
				ft.	pieces	lbs.
2	2.360	2.150	2.42	800	80	1936
2½	2.857	2.557	4.28	400	40	1712
3	3.476	3.176	5.26	300	30	1578
3½	3.971	3.671	6.12	250	25	1530
4	4.466	4.166	6.82	200	20	1364

*Note: SpeedCouple IMC shall be listed to safety standards UL-1242 and UL-514B. Manufactured in accordance with ANSI C80.6.

WEIGHTS, DIMENSIONS AND PACKAGING FOR SPEEDCOUPLE ON 90° ELBOWS

TRADE SIZE	MIN. RADIUS	OFFSET	STRAIGHT	WEIGHT PER ELBOW	WEIGHT PER ELBOW WITH COUPLING	STANDARD CARTON QTY.
	in.			Each	Each	
2	9.5	14.54	5.04	6.70	7.58	5
2½	10.5	17.00	6.50	12.00	13.76	Bulk
3	13	19.67	6.67	19.00	20.98	Bulk
3½	15	22.72	7.72	28.00	30.65	Bulk
4	16	23.94	7.94	31.00	34.09	Bulk
5	24	34.90	10.90	68.00	71.97	Bulk

Note: SpeedCouple with elbows shall be listed to safety standards UL-6 and UL-514B. Manufactured in accordance with ANSI C80.1.

Standard radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°

Special radius elbows: Available in 90°, 60°, 45°, 30°, 22.5°, 15°, 11.25°



227 W. Monroe Street, 26th Floor
Chicago, IL 60606
P 800.257.8182
F 312.275.1596

info@wheatland.com
wheatland.com
Follow us on Twitter:
@WheatlandTube



Wheatland Tube
JMC STEEL GROUP