



TYPE - NMFG

Flexible Liquidtight Nonmetallic Conduit
Food Grade



Trade Size	Type	Internal Diameter (In.)		Outer Diameter (In.)		Inside Bend Radius	Wt. Lbs. per 100 Ft.	Coil Length	Part Number
		Min.	Max.	Min.	Max.				
3/8"	NMFG-10	0.484	0.504	0.690	0.710	2"	10	100	81701
1/2"	NMFG-11	0.622	0.642	0.820	0.840	3.25"	11	100	81711
3/4"	NMFG-12	0.820	0.840	1.030	1.050	4.25"	15	100	81712
1"	NMFG-13	1.041	1.066	1.290	1.315	6.5"	25	100	81713
1-1/4"	NMFG-14	1.380	1.410	1.630	1.660	8"	34	100	81714
1-1/2"	NMFG-15	1.575	1.600	1.865	1.900	9"	42	50	81715
2"	NMFG-16	2.020	2.045	2.340	2.375	11"	60	50	81716

CONSTRUCTION:

Type NMFG is a helically wound integral Type B construction. It contains a spiral of rigid PVC reinforcement imbedded within the Flexible PVC wall. The PVC used is an FDA approved compound.

APPLICATION:

Type NMFG is intended for installation in accordance with Article 356 of the NEC (ANSI/NFPA-70) for Flexible Liquidtight Nonmetallic Conduit (LFNC-B or FNMC-B).

This conduit is intended to be used for "Splash Zone" food and beverage contact per FDA CFR21 and NSF 51/61 requirements. It is intended for a variety of wiring application on food processing equipment or clean rooms requiring motion, vibration and bending.

- Smooth exterior for easy wash down
- Resistant to Bleach (Sodium Hypochlorite)
- Will not promote bacteria growth
- Intended for use with Standard Nonmetallic or Metallic Liquidtight Connectors

WORKING TEMPERATURES:

-30°C to 80°C Dry / 60°C Wet / 70°C Oil

Standard Color: White



Listed File #E79308. Conforms to Underwriters Laboratories Standard ANSI/UL 1660 type B.



Certified File #LL230485. Conforms to CSA 22.2 No. 227.2 type B.

electri-flex company

222 W Central Ave. Roselle IL (USA) 60172-1994 (800) 323-6174 FAX (630) 529-0482
www.electriflex.com
NMFG - 08/15