



Model SLM600 shown with mounting base options (ordered separately)

► Model SLM600 **LED**

StreamLine® Modular Multifunctional High Output LED Combination Audible/Visual Signal

Multiple input technology allows for three levels of alarm. **A B C G R**

Model SLM600 is a multifunctional LED beacon and sounder combination developed with a multiple input technology that allows three separate levels of alarm (alert, pre-alarm, alarm) controllable via independent electric contacts.

Channel 1 includes a simulated strobe (triple flash) visual signal only. Channel 2 adds an audible tone, selectable from 32 tones via dip switch, to the simulated strobe effect. Channel 3 includes a steady light and a second, unique tone selectable from 32 different tones, for a total of 64 unique tones.

The volume of a selected tone is adjustable (65dB(A)-115dB(A) for the highest performing tone). Its enclosure is made from a self extinguishing polycarbonate material with high impact and UV resistance.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
- PLC compatible with PNP or NPN connections*
- 3 Channels included
 - 1: Visual only
 - 2: Visual + tone 1
 - 3: Visual + tone 2
- 100,000 hour LED
- Five color options
- Five mounting base options
- Type 3R, IP65
- CE Compliant
- UL and cUL listed

*Voltage and PLC connections are dependent on selected base.

MODEL	VOLTAGE	FLASH RATE/MINUTE (FLASH MODE)	DECIBELS @ 1M	
			MIN.	MAX.
SLM600 *	12-24VAC/DC	85 (+/-10)	65	115
	120-240VAC	85 (+/-10)	65	111

* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green or (R) Red

MAXIMUM OPERATING CURRENT (mA)			
12 VDC/DC	24 VDC/DC	120 VAC	240 VAC
380	460	100	60


StreamLine® Modular Multifunctional LED Combination Audible/Visual Signal (SLM600)

SPECIFICATIONS











Lamp Life:	100,000 Hours	100,000 Hours
Light Source:	LED Array	LED Array
Operating Temperature:	-22°F to 122°F	-30°C to 50°C
Weight (unit(s) + base = total weight)		
SLM600	19.05 oz.	0.54 kg
Shallow base	2.12 oz.	0.06 kg
Deep Base		
12-24 VDC/AC	4.23 oz.	0.12 kg
120-240 VAC	6.0 oz.	0.17 kg
Wall Mount		
12-24 VDC/AC	6.70 oz.	0.19 kg
120-240 VAC	8.47 oz.	0.24 kg
Pipe Mount		
12-24 VDC/AC	5.29 oz.	0.15 kg
120-240 VAC	6.70 oz.	0.19 kg
Twin Wall Mount		
12-24 VDC/AC	9.17 oz.	0.26 kg
120-240 VAC	12.35 oz.	0.35 kg

HOW TO ORDER

- Specify model number SLM600 and color
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG1)
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)



MOUNTING BASE OPTIONS

	Model Number	Base Color	Voltage	
 Shallow Base	SLMBS-012-024GY	Gray	12-24VDC/AC	
 Deep Base	SLMBD-012-024GY	Gray	12-24VDC/AC	
	SLMBD-PNP-012-024GY	Gray	12-24VDC/AC	
	SLMBD-012-024R	Red	12-24VDC/AC	
	SLMBD-120-240GY	Gray	120-240VAC	
	SLMBD-120-240R	Red	120-240VAC	
 Wall Mount	SLMBW-012-024GY	Gray	12-24VDC/AC	
	SLMBW-PNP-012-024GY	Gray	12-24VDC/AC	
	SLMBW-120-240GY	Gray	120-240VAC	
 Pipe Mount	SLMBP-012-024GY	Gray	12-24VDC/AC	Pipe Mount comes standard with 1/2" NPT Adapter 
	SLMBP-PNP-012-024GY	Gray	12-24VDC/AC	
	SLMBP-120-240GY	Gray	120-240VAC	
 Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VDC/AC	
	SLMBT-PNP-012-024GY	Gray	12-24VDC/AC	
	SLMBT-120-240GY	Gray	120-240VAC	